

Mock Exam 1

ETH Zurich

November 8,9 2010

Name: _____

Group: _____

1 Terminology (10 points)

Goal

This task will test your understanding of the object-oriented programming concepts presented so far in the lecture. This is a multiple-choice test.

Todo

Place a check-mark in the box if the statement is true. There may be multiple true statements per question; 0.5 points are awarded for checking a true statement or leaving a false statement un-checked, 0 points are awarded otherwise.

1. A command...

- a. call is an instruction.
- b. may modify an object.
- c. may appear in the precondition and the postcondition of another command but not in the precondition or the postcondition of a query.
- d. may appear in the class invariant.

2. The syntax of a program...

- a. is the set of properties of its potential executions.
- b. can be derived from the set of its objects.
- c. is the structure and the form of its text.
- d. may be violated at run-time.

3. A class...

- a. is the description of a set of possible run-time objects to which the same features are applicable.
- b. can only exist at runtime.

- c. cannot be declared as expanded; only objects can be expanded.
 - d. may have more than one creation procedure.
4. Immediately before a successful execution of a creation instruction with target x of type C ...
- a. $x = Void$ must hold.
 - b. $x \neq Void$ must hold.
 - c. the postcondition of the creation procedure may not hold.
 - d. the precondition of the creation procedure must hold.
5. Void references...
- a. cannot be the target of a successful call.
 - b. are not default values for any type.
 - c. indicate expanded objects.
 - d. can be used to terminate linked structures (e.g. linked lists).

2 Design by Contract (10 Points)

Class *PERSON* is part of a software system that models marriage relations between persons. The following rules do not necessarily have universal value but describe a particular set of rules for marriage at a particular time and place in the past, e.g. Canton Zürich 1900:

1. Every person has a nonempty name.
2. A person cannot be married to himself/herself.
3. If a person X is married to a person Y, then Y is married to X.
4. In order for a person X to be able to marry a person Y, neither X nor Y may be already married.
5. Divorces are not allowed.

Your task is to fill in the contracts of the class (preconditions, postconditions and class invariant) according to the specification given. You are not allowed to change the class interfaces or any of the already given implementations. Note that the number of dotted lines does not indicate the number of necessary code lines that you have to provide.

```
class PERSON
2
3   create make
4
5   feature {NONE} -- Creation
6
7       make (n: STRING)
8           -- Create a person with a name 'n'.
9           require
10
11 .....
12 .....
13 .....
14
```

```
16 .....
18     do
19         -- Create a copy of the argument and assign it to 'name'
20         name := n.twin
21     ensure
22 .....
24 .....
26 .....
28 .....
30     end
32 feature -- Access
33
34     name: STRING
35         -- Person's name.
36
37     spouse: PERSON
38         -- Spouse if a spouse exists, Void otherwise.
39
40 feature -- Status report
41
42     is_married: BOOLEAN
43         -- Is person married?
44     do
45         Result := (spouse /= Void)
46     ensure
47 .....
48 .....
50 .....
52 .....
54 .....
56     end
58 feature {PERSON} -- Implementation
59
60     accept_marriage (p: PERSON)
61         -- Set 'spouse' to 'p', who is already married to you.
62     require
63 .....
64 .....
66 .....
```

```
68 .....
70 .....
72     do
       spouse := p
74     ensure
76 .....
78 .....
80 .....
82     end
84 feature -- Basic operations
86     marry (p: PERSON)
       -- Marry 'p'.
88     require
90 .....
92 .....
94 .....
96 .....
98     do
       spouse := p
       p.accept_marriage (Current)
100    ensure
102 .....
104 .....
106 .....
108     end
110 invariant
112 .....
114 .....
116 .....
118 .....
```

```
120 .....
122 .....
end
```

3 Digital root (10 points)

The *digital root* (Quersumme) of a number is found by adding together the digits that make up the number. If the resulting number has more than one digit, the process is repeated until a single digit remains.

Example input and output

Input	Digital root	Example
123	6	= 1 + 2 + 3
5720	5	= 1 + 4 ← 14 = 5 + 7 + 2 + 0
99999999	9	
8	8	

Your task in this problem is to implement a function that, given a non-negative number, calculates the digital root and returns it as the result. Fill in the body of function *digital_root* below. Your implementation should work with *INTEGER* objects only. You might find the following two operators of class *INTEGER* useful: `\%` (modulo) and `//` (integer division).

There exists a closed-form solution to this problem: $digital_root(n) = n - n \lfloor \frac{9}{n} \rfloor$. You are not allowed to use this to solve this programming exercise!

```
digital_root (a_number: INTEGER): INTEGER
2   -- Digital root (Quersumme) of 'a_number'
   require
4   a_number_positive: a_number >= 0
   local
6
8
10
12  do
14
16
18
20
22
24
```

```
26 .....  
28 .....  
30 .....  
32 .....  
34 .....  
36 .....  
38 .....  
40 .....  
42 .....  
44 .....  
46 .....  
48 .....  
50 .....  
52 .....  
54 .....  
56 .....  
58 .....  
60 .....  
62 ensure  
   result_in_range : 0 <= Result and Result <= 9  
end
```

4 Inversion of Linked List (10 Points)

The classes *SINGLE_LINKED_LIST* [G] and *SINGLE_CELL* [G] implement a single linked list. The first cell of the list is stored in the attribute *first* of the class *SINGLE_LINKED_LIST* [G]. Attribute *next* of class *SINGLE_CELL* [G] delivers the next cell . Calling *next* on the last cell will return a *Void* reference.

Implement the feature *invert* of class *SINGLE_LINKED_LIST* [G], so that it inverts the order of the elements in the list. For example, inverting the list [6, 2, 8, 5] results in [5, 8, 2, 6]. **Do not** create new objects of type *SINGLE_CELL* [G] and also **do not** introduce any new feature in class *SINGLE_LINKED_LIST* [G] and *SINGLE_CELL* [G].

```
class
2  SINGLE_LINKED_LIST [G]
4 feature -- Access
6  first : SINGLE_CELL [G]
   -- Head element of the list, 'Void' if the list is empty
8
   feature -- Basic operations
10
   invert
12   -- Invert the order of the elements of the list .
   -- E.g. the list [6, 2, 8, 5] should be become [5, 8, 2, 6].
14   local
16   .....
18   .....
20   .....
22   do
24   .....
26   .....
28   .....
30   .....
32   .....
34   .....
36   .....
38   .....
40   .....
42   .....
44   .....
46   .....
   end
48 end
```

```
class
2  SINGLE_CELL [G]

4 feature -- Access

6  next: SINGLE_CELL [G]
   -- Reference to the next generic list cell of a list
8

10 feature -- Element change

12  set_next (an_element: SINGLE_CELL [G])
   -- Set 'next' to 'an_element'.
14  ensure
   next_set: next = an_element
16
end
```