

Assignment 7: Lock-free approaches

ETH Zurich

1 Concurrent Logger

1.1 Background

Your company is developing an application server, which, for security reasons, has to log every action. The log is stored in memory and crawled by various intrusion detection algorithms. Since the current logger uses a lock—which is obviously a performance bottleneck—you decided to rewrite it using lock-free techniques.

A log entry contains a date and a message. The date, which also contains the time, is represented as a long integer. The message is a string. Adding a log entry should not require traversing the whole log.

Java provides several classes that support atomic compare-and-set, in particular, *AtomicLong* to store long integers, and *AtomicReference<V>* to store references such as String. These classes have three important methods:

```
// Atomically sets the value to the given updated value if the current value == the
// expected value. Returns true if successful.
boolean compareAndSet (V expect, V update);

//Gets the current value.
V get();

//Sets to the given value.
void set(V newValue);
```

1.2 Task

Your task is to implement this logger according to the interface below, without using locks:

```
public interface Logger {
    //Adds a new log entry
    void addLogEntry (long date, String message);
}
```

Hint: The data structure for the log should not have a fixed capacity and it should be possible to add retrieving and pruning methods later. You may define as many classes as you need for completing the task.

2 Spin Lock

2.1 Background

A spinlock^[1] is a simple (but not very efficient) lock-free algorithm in which a thread trying to acquire a lock is made to wait in a loop while checking if the lock is free. It is an example of

a busy-waiting algorithm because the thread waiting in the loop is not idle, but not doing any useful work either.

2.2 Task

Your task is to write fill in the pseudocode for the *acquire* and *release* methods of the spinlock class given below. Assume that there is a function *compare_and_swap(target, old, new)*.

```
class SPINLOCK
2
  feature locked: INTEGER
4
  feature make
6    do
      -- write your code here.
8    end

10  feature acquire
      do
12    -- write your code here.
      end
14
  feature release
16    do
      -- write your code here.
18    end
end
```

3 Atomic update of multiple values

3.1 Background

An online game with thousands of players features a daily high score. The high score consists of the player's name and the score he or she achieved. Profiling determined that the current lock-based implementation is a bottleneck.

3.2 Task

You are asked to provide a prototype of a lock-free solution, pseudo-code is sufficient. You can use an integer for the score. Provide a routine to update the high score if the new score is better and a routine to retrieve the current high score. If you need additional data structures, describe them as well.

You may use atomic CAS: assume that there is a function *compare_and_swap(target, old, new)*.

References

- [1] <http://en.wikipedia.org/wiki/Spinlock>